
## SY-M50W

# High Efficiency, High Quality PV Module

Electrical Characteristics	SY-M50W
Maximum power (Pmax)	50W
Voltage at Pmax (Vmp)	18.2V
Current at Pmax (Imp)	2.75A
Open-circuit voltage (Voc)	22.6V
Short-circuit current (Isc)	2.95A
Temperature coefficient of Voc	-(0.40 ± 0.05)%/ °C
Temperature coefficient of Isc	(0.065 ±0.01)% /°C
Temperature coefficient of power	-(0.5±0.05)%/ °C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	600V DC
Power tolerance	+ 3%
Cells	multicrystalline silicon solar cell
No. of cells and connections	36(4X9)
Module Dimension	670mm[26.38in.]x530mm[20.87in.]x25mm[0.98in.]
Weight	4.20kg[9.24lbs]

<sup>\*</sup> STC:Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C

### **Module Diagram**




Dimensions in brackets are in inches.
Un-bracketed dimensions are in millimeters.
Unit:mm[in.]




Junction Box Top View (Lid open)



## I-V Curves











#### **Key Features:**

- High module efficiency and stable power output
- Based on leading process technology
- Outstanding electrical performance under high temperature conditions or low irradiance conditions
- Easy of installation and all-weather applications
- 5 years product warranty(materials and workmanship)
- 20 years module power output warranty
- Peak power of single module is guaranteed in +3% power tolerance
- Strong framed module, passing loaded test of 5400 Pa (IEC61215 2nd)
- The manufacture is certified for ISO 9001:2008

## **Product's Guarantee**

- 5 years products life warranty
- 15 years module power output no less 90%
- 20 years module power output no less 80%

## **Applications**

- Off grid residential roof-tops
- Off grid commercial/industrial roof-tops
- Rural area applications
- Solar power system
- Other off-grid applications



## SUNYOOO Solar Technology

**Address:** Youyi Village, Luoyang Town, Wujin District, Changzhou, Jiangsu,P.R.China

 Tel:
 86-519-88790861

 86-519-88791962

 Fax:
 86-519-88792861

 E-mail:
 sales @sunyooo.com

 Website:
 www.sunyooo.com

<sup>\*</sup> Specifications are subject to change without notice at any time.